
Spécifications







Eaton 072894

Eaton Moeller® series NHI Standard auxiliary contact, 2N/O+1N/C, screw connection

Spécifications générales	
PRODUCT NAME	Eaton Moeller® series NHI Accessory Standard auxiliary contact
CATALOG NUMBER	072894
MODEL CODE	NHI21-PKZ0
EAN	4015080728948
PRODUCT LENGTH/DEPTH	68 mm
PRODUCT HEIGHT	90 mm
PRODUCT WIDTH	15 mm
PRODUCT WEIGHT	0.038 kg
CERTIFICATIONS	CSA Class No.: 3211-05 CE UL 508 CSA-C22.2 No. 14 UL Category Control No.: NLRV IEC/EN 60947-4-1 CSA UL UL File No.: E36332 CSA File No.: 165628
CATALOG NOTES	Can be retrofitted on the right side of motor-protective circuit-breakers

Powering Business Worldwide

Features & Functions

FEATURES	Interlocked opposing contacts

General

LIFESPAN, ELECTRICAL	50,000 Operations
MODEL	Top mounting
MOUNTING METHOD	Side mounting
OVERVOLTAGE CATEGORY	III
POLLUTION DEGREE	3
PRODUCT CATEGORY	Accessories
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	6000 V AC
USED WITH	Motor protective circuit-breaker

Climatic environmental conditions

AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
AMBIENT OPERATING TEMPERATURE - MAX	55 °C

Terminal capacities

TERMINAL CAPACITY (SOLID/FLEXIBLE WITH FERRULE)	0.75 - 1.5 mm²
TERMINAL CAPACITY (SOLID/STRANDED AWG)	18 - 14, Screw terminals

Electrical rating

RATED OPERATIONAL CURRENT (IE)	1 A at AC-15, 440 V 500 V
RATED OPERATIONAL CURRENT (IE) AT AC-15, 220 V, 230 V, 240 V	3.5 A
RATED OPERATIONAL CURRENT (IE) AT AC-15, 380 V, 400 V, 415 V	2 A
RATED OPERATIONAL CURRENT (IE) AT DC-13, 110 V	0.5 A
RATED OPERATIONAL CURRENT (IE) AT DC-13, 220 V, 230 V	0.25 A
RATED OPERATIONAL CURRENT (IE) AT DC-13, 24 V	2 A
RATED OPERATIONAL CURRENT (IE) AT DC-13, 60 V	1 A
RATED OPERATIONAL VOLTAGE (UE) AT AC - MAX	500 V
RATED OPERATIONAL VOLTAGE (UE) AT DC - MAX	250 V
SAFE ISOLATION	440 V, Between auxiliary contacts and main contacts, According to EN 61140

Contacts

CONTROL CIRCUIT RELIABILITY	< 2 λ, < 1 failure at 100,000,000 Operations (at U_e = 24 V DC, Umin = 17 V, Imin = 5.4 mA)
NUMBER OF CONTACTS (CHANGE-OVER CONTACTS)	0
NUMBER OF CONTACTS (NORMALLY CLOSED CONTACTS)	1
NUMBER OF CONTACTS (NORMALLY OPEN CONTACTS)	2

SHORT-CIRCUIT PROTECTION RATING WITHOUT WELDING	10 A gG/gL, Fuse, Auxiliary contacts

Design verification

EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	0 W
HEAT DISSIPATION CAPACITY PDISS	0 W
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	0.04 W
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	3.5 A
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	0 W
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL	Is the panel builder's

Ressources

CHARACTERISTIC CURVE	121U003 eaton-motorstarters-auxiliary-contact-nhi-accessory-characteristic-curve-005.eps
DECLARATIONS OF CONFORMITY	DA-DC-00005072.pdf
ECAD MODEL	ETN.072894.edz DA-CE-ETN.NHI21-PKZ0
INSTRUCTIONS D'INSTALLATION	IL03402034Z eaton-front-mounted-auxiliary-contact-nhi-il03801004z.pdf IL03407011Z.pdf
MCAD MODEL	DA-CD-nhi_pkz0 eaton-cadenas-path-01-geo-nhi_pkz0.3db eaton-cadenas-side_view-nhi_pkz0_side.pra eaton-cadenas-front_view-nhi_pkz0_front.pra DA-CS-nhi_pkz0
SCHÉMAS	eaton-manual-motor-starters-auxiliary-contact-nhi-accessory-dimensions-002.eps 121X006 121I005 eaton-manual-motor-starters-auxiliary-contact-nhi-accessory-3d-drawing-003.eps 121O003 eaton-manual-motor-starters-auxiliary-contact-nhi-accessory-3d-drawing-005.eps
SCHÉMAS ÉLECTRIQUES	121S011 eaton-manual-motor-starters-contact-nhi-accessory-wiring-diagram.eps

ELECTRICAL CIRCUITS AND CONNECTIONS	responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Irlande
Eaton.com

© 2025 Eaton. Tous droits

Eaton est une marque déposée.

Toutes les autres marques commerciales appartiennent à leur propriétaire respectif.

Follow us on social media to get the latest product and support information.

réservés.

